



Pos	Qty	Part No.	Description	Ordernumber
1	1	900053	Muffler HyperFox Ov120 S150 Shot Blasted	YA10F01-HFSB - Shot Blasted
1	1	900089	Muffler HyperFox Ov120 S150 Carbon Steel	YA10F01-HFCS - Carbon Steel
1	1	900063	Muffler HyperFox Ov120 S150 Black Coated	YA10F01-HFBC - Black Coated
		80227	Mounting Parts:	Weight:
2	1	72193	Link Pipe	Stock: 7,2 kg Bos: 4,3 kg
3	1	64449	Mounting Bracket	Noiselevel: @ 5500 rpm
4	2	14140	Bolt M6x16	Stock: Specified 95,0 dB(A)
5	1	14076	Washer M10	Measured 93,8 dB(A)
6	1	14077	Nut M10x1,25	Bos: Ec appr. 96,2 dB(A)
7	2	14087	Pull Spring 48 mm.	Open 101,9 dB(A)
8	1	64576	Clamp 63	
9	1	64522	Standstop (optional)	
Performance				
Stock: 133,8 Hp / 10926 rpm				
Bos: 137,9 Hp / 10898 rpm				
Max. Hp incr.: + 5,2 Hp / 10278 rpm				
Max Nm incr.: + 7,2 Nm / 2542 rpm				
Extra Parts:				Tips
		650079	DBeater Ø 32 Hyper Restriction	In order to avoid smudges and fingerprints burning into the surface it is imperative to clean the exhaust before starting the engine, burnt in stains are very difficult to remove. After 300 miles or 500 kms. check all nuts and bolts and retighten if necessary.