



Approval Number

E13 92R-01 10376 TYPE 1015

Pos	Qty	Part No.	Description	Ordernumber
1	1	900060	Muffl. DesertFox Type 1015 Shot Blasted	SU10D02-DESB - Shot Blasted
1	1	900061	Muffl. DesertFox Type 1015 Carbon Steel	SU10D02-DECS - Carbon Steel
1	1	900062	Muffl. DesertFox Type 1015 Black Coated	SU10D02-DEBL - Black Coated
Mounting Parts:				Weight:
2	1	72304	Adapter	Stock: 5,5 kg
3	1	64768	Mounting Bracket #1	Bos: 4,3 kg
4	1	64769	Mounting Bracket #2	Noiselevel: @ 4000 rpm
5	4	14148	M6x16 Torx Flange Screw	Stock: Specified 89,0 dB(A)
6	0	Original	Bolt M8 original	Measured 89,0 dB(A)
7	0	Original	Washer M8 original	Bos: Measured 90,5 dB(A)
8	2	14088	Pull Spring 36 mm.	
9	1	64020	Clamp 57	
				Performance
				Stock: 90,2 Hp / 7384 rpm
				Bos: 92,4 Hp / 7402 rpm
				Max. Hp incr.: + 2,8 Hp / 5799 rpm
				Max Nm incr.: + 3,8 Nm / 5634 rpm

Extra Parts:

Tips

In order to avoid smudges and fingerprints burning into the surface it is imperative to clean the exhaust before starting the engine, burnt in stains are very difficult to remove.

After 300 miles or 500 kms. check all nuts and bolts and retighten if necessary.